

**RECEIVED
CENTRAL FAX CENTER**

U.S. Serial No. 09/761,203
Response to the Office action of January 2, 2008

APR 29 2008

This listing of claims will replace all prior versions, and listings, of claims in the application:

The Status of the Claims

1. (Currently Amended) An apparatus for displaying the status of a digital video recording device, comprising:
a receiver for receiving a broadband video signal from a provider;

a memory for storing a plurality of selectable status parameters indicating functionality of the digital video recording device, wherein one of said plurality of selectable status parameters is [[an]]a remaining recording time out of disk space alert user setting received from a user of the digital video recording device; and

a processor for generating a display of the broadband video signal and for controlling a display of said plurality of status parameters based on received commands to access said memory, so as to display at least a selected one of the plurality of status parameters.
2. (Original) The status display apparatus of claim 1, wherein an interface enables a user to send said commands to display said selected status parameter via said processor.
3. (Original) The status display apparatus of claim 2, wherein said interface is selected from a remote control device, or from execution keys or buttons provided on the digital video recording device.
4. (Original) The status display apparatus of claim 1, wherein said memory and processor are contained within the digital video recording device.

U.S. Serial No. 09/761,203

Response to the Office action of January 2, 2008

5. (Original) The status display apparatus of claim 1, wherein said processor controls display of a status menu for selection of at least one the plurality of status parameters based on reception of a command to display the status menu by a user.

6. (Original) The status display apparatus of claim 5, wherein the user manipulates keys of a remote control to transmit commands to said processor to display said status menu on a display device operatively connected to the digital video recording device, and further manipulates said remote control to graphically select a status parameter from said displayed status menu for display.

7. (Original) The status display apparatus of claim 1,
wherein a user manipulates designated keys or buttons of a remote control device, each designated key or button corresponding to each of said selectable plurality of status parameters, and

wherein the manipulated key or button causes the correspondingly selected status parameter to be displayed on a display device operatively connected to the digital video recording device.

8. (Original) The status display apparatus of claim 1,
wherein a user manipulates designated keys or buttons provided on the digital video recording device, each designated key or button corresponding to each of said selectable plurality of status parameters, and

wherein the manipulated key or button causes the correspondingly selected status parameter to be displayed on a display device operatively connected to the digital video recording device.

U.S. Serial No. 09/761,203

Response to the Office action of January 2, 2008

9. (Currently Amended) The status display apparatus of claim ~~[[27]]~~1, wherein one of said plurality of selectable status parameters is a current delay feature which displays how far a recording is behind a live broadcast when a signal corresponding to the live broadcast is paused.

10. (Currently Amended) The status display apparatus of claim ~~[[1]]~~9, wherein the current delay feature is displayed as at least one of an icon, pie-chart and text message form.

11. (Original) The status display apparatus of claim 1, wherein one of said plurality of selectable status parameters is a live/recorded status feature that displays whether a program being viewed is either live or recorded.

12. (Original) The status display apparatus of claim 11, wherein the word "LIVE" or "RECORDED" is displayed in flashing form for a finite period of time, depending on the status of the program being viewed.

13. (Currently Amended) The status display apparatus of claim 1, wherein one of said plurality of selectable status parameters is a disk gas ~~[[gage]]~~gauge feature indicating how much of a mass storage device operatively connected to the digital video recording device is consumed by recorded material.

14. (Original) The status display apparatus of claim 13, wherein said disk gas gauge feature is displayed in at least one of icon, pie-chart and bar-graph form and indicates the percent of the mass storage device capacity used; and/or the percent of the mass storage device capacity that is unused.

U.S. Serial No. 09/761,203

Response to the Office action of January 2, 2008

15. (Original) The status display apparatus of claim 13, wherein said disk gas gauge feature is displayed in at least one of icon, pie-chart and bar-graph form and indicates the available recording time remaining before the mass storage device is full.

16. (Original) The status display apparatus of claim 13, wherein said mass storage device is selected from the group comprising at least a hard disk drive, a magnetic storage device and an optical storage device.

17. (Original) The status display apparatus of claim 1, wherein one of said plurality of selectable status parameters is a notification indicating the approximate minutes of recording time still available while recording is in progress.

18. (Cancelled)

19. (Cancelled)

20. (Cancelled)

21. (Original) The status display apparatus of claim 17, wherein said notification indicating the approximate minutes of recording time still available is displayed as an animated icon on a display device operatively connected to the digital video recording device.

22. (Original) The status display apparatus of claim 18, wherein said out-of-disk space alert has both a video and audio component.

U.S. Serial No. 09/761,203

Response to the Office action of January 2, 2008

23. (Currently Amended) The status display apparatus of claim 1, wherein one of said plurality of selectable status parameters is a notification indicating the program length of a desired program to record and the approximate minutes of recording time still available [[while]] for recording.

24. (Original) The status display apparatus of claim 23, wherein said notification is automatically displayed prior to or at the start of recording the desired program.

25. (Original) The status display apparatus of claim 24, wherein said notification is displayed as text message on a display device operatively connected to the digital video recording device.

26. (Original) The status display apparatus of claim 1, wherein one of said plurality of selectable status parameters is an attributes list which directs the user to other status parameters for display and manipulation, said other status parameters including at least one of a date a program is recorded, a latest date that a stored program has been accessed, size of a recorded or live program, length of a live or recorded program, protect feature to prevent erasure of a recorded program, save options designating how much of a program is to be recorded and/or how long of a time a program is to be stored before being erased, and implementation of a hidden file feature to prevent titles of certain programs from being displayed on a program guide list.

U.S. Serial No. 09/761,203

Response to the Office action of January 2, 2008

27. (Currently Amended) A method of displaying the status of a digital video recording device on a display device operatively connected thereto, comprising:

receiving a broadband video signal from a provider;

storing a plurality of selectable status parameters indicating functionality of the digital video recording device within a memory of the digital video recording device, wherein one of said plurality of selectable status parameters is [[an]]a remaining recording time out of disk space alert user setting received from a user of the digital video recording device;

receiving commands to display at least a selected one of the plurality of status parameters; and

accessing said memory to display said broadband video signal and to display said selected one of the plurality of status parameters on the display device based on said received commands.

28. (Original) The status display method of claim 27, further comprising controlling display of a status menu on said display device for selection of at least one the plurality of status parameters based on said received commands.

29. (Original) The status display method of claim 28, further comprising transmitting said received commands by manipulating keys of a remote control so as to display said status menu on said display device, and further manipulating said keys to graphically select a status parameter from said displayed status menu for display.

U.S. Serial No. 09/761,203
Response to the Office action of January 2, 2008

30. (Original) The status display method of claim 27, further comprising manipulating designated keys or buttons of a remote control device, each designated key or button corresponding to each of said selectable plurality of status parameters, wherein the manipulated key or button sends said command to display said selected status parameter on said display device.

31. (Original) The status display method of claim 27, further comprising manipulating designated keys or buttons provided on the digital video recording device, each designated key or button corresponding to each of said selectable plurality of status parameters, wherein the manipulated key or button sends said command to display said selected status parameter on said display device.

32. (Currently Amended) In a system having a digital video recording device, an apparatus for displaying the status of the digital video recording device on a display device operatively connected to the digital video recording device, comprising:

a receiver to receive a broadband video signal from a provider;

a memory for storing a plurality of selectable status parameters indicating functionality of the digital video recording device, wherein one of said plurality of selectable status parameters is [[an]]a remaining recording time out of disk space alert user setting received from a user of the digital video recording device; and

a processor for controlling a display of said plurality of status parameters based on received commands to access said memory so as display at least a selected one of the plurality of status parameters.

33. (Original) The system of claim 32, wherein said memory and processor are contained within the digital video recording device.

U.S. Serial No. 09/761,203
Response to the Office action of January 2, 2008

34. (Previously Presented) A method as defined in claim 27, further comprising displaying an out of disk space alert when an available recording capacity is less than or equal to the out of disk alert user setting.

35. (Previously Presented) A method as defined in claim 27, wherein the out of disk space alert user setting includes two or more values at which an out of disk space alert should be presented.

36. (New) A method as defined in claim 1, wherein the processor is further to:

- receive a request to record a television program;
- compare an amount of available disk storage space to an amount of time needed to record the program to determine a remaining disk storage space;
- compare the remaining disk storage space to the disk space alert user setting; and
- display an out of disk space alert based on the comparison.